



BS 25 Pro

Top Quality Tray Sealer with Vacuum and Gas Injection

BS 25 Pro



BS 25 Pro	
Kinematical speed (cycles/min)	Up to 2
Max film width (mm)	410
Max container height (mm)	115
Machine dimensions (L x W x H, mm)	1140 x 640 x 1500
Electrical supply	380V, 3-phase, 50 Hz
Power (kW)	2,3
Vacuum pump (m³/h)	40
Machine weight (kg)	205
Sealing tool compatibility	BS 25 Basic, BS 10 Eco

The **BS 25 Pro** is a semi-automatic tray sealing machine with vacuum and gas injection.

Economical in electrical power consumption. With automatic film trim rewind after sealing.

Suitable for a wide range of sealing applications such as: fresh or frozen meat & fish, fresh agricultural products, bakery products, prepared meals, nuts, dairy products, and so on.

General Features:

- Made of stainless steel and anodized aluminum.
- Easy change from one container to another within minutes.
- BUSCH vacuum pump.
- **SIEMENS PLC** with a 7" touch screen.
- Production scheduling with program and parameter memory slots.
- Low power consumption.
- Compact in size.

Optional:

- Safety valve for gas mixtures with a high oxygen content (O₂> 21%).
- **SkinPack** technology.
- **High-SkinPack** technology.
- Lifting system with pushers for sealed container discharge.
- Photocell for printed film.
- System for automatic drawer movement.