

# Euro 600 & Euro 600 BB TR

## Flowpack - Horizontal Packaging Machine

### Euro 600 BB TR



The position of the film is either above or below the product feeding conveyor (custom-made).

Extremely suitable for large, sensitive, various sized products, packed one by one or more than one together (behaving as a single product). It performs perfectly hermetic sealing, even at maximum operating speed. Equipped with 6 servo motors and 4 additional asynchronous motors.

The **Euro 600 BB TR** version works with a box-motion mechanism; thus, it is suitable for modified atmosphere packaging (MAP) or for injection of alcohol, perfume etc. The same mechanism is also able to scan products of different size and track their length via photocells.

#### General Features:

- 100% stainless, robust construction.
- Control panel with 7.7-inch color touch screen.
- 100 programmable memory slots.
- Mechanical film unwinding.
- Electronic circuit console with high quality components, in accordance with European Union directives for 24V connections.
- Made in Europe.

#### Optional:

- Printer.
- Gas injection (MAP), perfume spraying etc.
- Product detection (no product – no bag).
- Changing bag length, depending on the length of the product.
- Maximum film width 720 mm.
- Gusseted bag.
- Fixed or adjustable forming device.
- Extended feeding conveyor.
- Film preheating.
- Lots of additional customizations.

### Euro 600

<b>Kinematical speed (pcs/min)</b>	80
<b>Max film width (mm)</b>	600
<b>Max bag width (mm)</b>	280
<b>Max bag length (mm)</b>	unlimited
<b>Max external film reel dimension (mm)</b>	350
<b>Air consumption (lt/min)</b>	50, at 6 bar
<b>Electrical supply (V)</b>	380
<b>Power (kW)</b>	12,5