



## KL4055 / KL4065 / KL5575

Semi-Automatic L-Sealers

## L-Sealer KL4055



	KL4055	KL4065	KL5575
Max product dimensions (Width x Length, mm)	350 x 500	400 x 550	500 x 700
Max product height (mm)	200	300	200
Electrical supply (V)	380	380	380
Power (kW)	2	2	2,2
Capacity (pcs/min)	8 - 15	10 - 20	8-15
Machine dimensions (Width x Length x Height mm)	1560 x 720 Xx1070	1500 x 730 x 950	2010 x 920 x 1070
Weight (kg)	160	190	200

The **OnShrink KL** semi-automatic L-sealers for Shrink Lines by Kapelis Packaging are of high quality and very affordable. Compatible with the **OnShrink KT** series shrink tunnels.

They are intended for applications where flexibility is required in the degree of automation of production.

The operator manually places the product in the cutting/sealing area. The L-sealer's function is triggered either manually (by pressing the corresponding button or foot pedal - optionally) or automatically (with set waiting and sealing times). Subsequently, the product is transferred to the shrink chamber through the integrated conveyor.

The machine is electronically controlled by a PLC.

They are always offered in a motorized version (without the need to buy a compressor).

## **General Features:**

- Protection of the operator: the cutter returns to its position when it encounters an obstacle (e.g., the operator's hand).
- Adjustable time & sealing temperature.
- Conveyor belt in the sealing area.
- Roller conveyor with silicone-coated rollers inside the chamber.
- Adjustable height.
- Very easy switch between different products.
- Stainless steel resistors.
- Compliance with EC regulations of the European Union.

## **Optional:**

• Automatic film trim collector.