

Maya Eco PN

Fast Vertical Packaging Machine suitable for sensitive products

Maya Eco PN



Compact and robust packaging machine, available in vertical configuration or with a fixed inclination. It is made of stainless steel to achieve the highest standards of hygiene and packaging quality. The pneumatic retention system and motorized film unfolding are offered as standard equipment. Its 7" color, easy-to-use display, the ability for quick replacement of the forming tube and the use of high-quality components, make the **Maya Eco** a benchmark among this machine category.

General Features:

- Stainless steel, robust construction.
- Very high performance compared to other similar machines, with a mechanical speed of up to 100 packages per minute in the servo version.
- Control panel with 7-inch color touch screen.
- Accepts all heat-seal materials such as polypropylene, suitable aluminum foil, PVC, laminated film, etc.
- Electronic circuit console with high quality components, in accordance with European Union directives for 24V connections.
- Made in Europe.

Optional:

- Printer.
- Modified atmosphere packaging (MAP).
- Automatic film centering.
- Square bottom unit.
- Stabilo unit.

Maya Eco PN

| | |
|---------------------------------------|-------------------|
| Kinematical speed (cycles/min) | 60/100 with servo |
|---------------------------------------|-------------------|

| | |
|---------------------------------|-----|
| Max film reel width (mm) | 350 |
|---------------------------------|-----|

| | |
|---|-----|
| Max film reel external diameter (mm) | 350 |
|---|-----|

| | |
|--|-------------|
| Compressed air consumption (lt/min) | 5, at 6 bar |
|--|-------------|

| | |
|------------------------------|---------|
| Electrical supply (V) | 220/380 |
|------------------------------|---------|

| | |
|-------------------|---|
| Power (kW) | 4 |
|-------------------|---|