

S4022 / S5522 / S8515

Automatic Step-Motion Shrinking Machines

Shrink machine S 4022 with shrinking tunnel KT2 5535,
 feed conveyor & discharge conveyor



Kapelis Packaging's **OnShrink S Series** automatic shrinking machines are very affordable.

They are distinguished for their performance and durability. Both the construction materials as well as the electronics (PLC Siemens) and the pneumatic system (FESTO) are of extremely high quality. They use folded film. Longitudinal sealing is continuous while transversal sealing is achieved with a guillotine (step motion). The two welding systems are independent of each other.

General Features:

- Three seal system.
- Ideal for frequent changes from product to product.
- Automatic detection of product presence, automatic detection of products of different length.
- Easy and fast changes between film rolls of different widths.
- Programmable PLC by Siemens and color touch screen.
- Easy to operate.
- Continuous temperature control.
- Suitable for Polyolefin (PO) & Polyethylene (PE) films.
- Double silicone screens on either side of the shrink chamber for optimal results.
- Dual insulation of the shrink chamber.
- Compliance with EC regulations of the European Union.

	S4022	S5522	S8515
Max product dimensions (Length x Width x Height, mm)	unlimited x 400 x 220	unlimited x 450 x 220	unlimited x 750 x 150
Productivity (pcs/min)	20 – 60	20 – 60	10 – 40
Electrical supply (V)	380	380	380
Power (kW)	3	4,2	5,2
Machine dimensions (Length x Width x Height mm)	207 x 173 x 143	222 x 188 x 143	253 x 235 x 133
Machine weight (kg)	750	1000	1200